



## Technical Data Sheet

### **K-TAK – DP 365/60 GLOSS WHITE FILM A3+**

#### Product Description

K-TAK – DP 365/60 GLOSS WHITE FILM A3+ is a high quality, self-adhesive sheets specifically produced for use on digital presses. Combining gloss white surface material with permanent adhesives to suit your needs.

#### Product Features

- With Hybrid Technology, suitable for Dry Toner and HP Indigo printing system
- Reliable feed and print quality on digital presses
- No residue during print and converting
- Excellent thermal stability and moisture resistance

#### Application

These products are optimized for use in the digital printing. Excellent transfer and anchorage of Electrolnk as used in the digital printing process. Adhesive is specifically designed to be compatible with a variety of printing methods and this product is used in a variety of labelling applications, when the advantages of digital printing on product which need high print quality.

#### Technical Data Specification

Product Construction	Type
Face Material	Gloss white polypropylene film with top coated
Adhesive type	Acrylic Solvent Base
Release Liner	Clay Coated Release Paper, White color with K-TAK Brand

Properties	Unit	Average Value	
Thickness	Face	$\mu\text{m}$	$58 \pm 3$
	Release	$\mu\text{m}$	$130 \pm 10$
Basic Weight	Face	gsm	$47 \pm 5$
	Release	gsm	$130 \pm 5$
Adhesion (S/Steel)	N/25 mm	$\geq 10$	
Loop tack	N/25 mm	$13.4 + 2.2$	
End user temperature	$^{\circ}\text{C}$	-20 up to 150	
Providing range (Minimum)	$^{\circ}\text{C}$	-25	

**PT. Multi Viscomindo**

Jl. Deplu Raya No. 7, Bintaro, Pesanggrahan – Jakarta 12330

Tel: +62 21 7376530 – Fax: +62 21 7363488

Email: sales@multiviscomindo.com



**Remarks:**

- |  |
|--|
| <ol style="list-style-type: none"><li>1. Peel adhesion and Loop tack value are measured by ASTM, FINAT and JIS test method ones under control condition (23 ± 2°C, 50 ± 5%) and not guaranteed.</li><li>2. Substrates to be applied and methods of application may be distinguishable.</li></ol> |
|--|

**Storage Condition:**

1. The product must be stored in shady (or cool) place and do not expose to sunlight directly.
2. To obtain best performance, use this product within one year from the date of manufacture.

The statements in this information sheet are based upon our knowledge and practical experience. This data is intended only as a source of information and is given without guarantee and does not constitute a warranty. Due to the wide variety of possible uses and applications, customers should independently determine the suitability of this material for their specific purpose, prior to use.

**PT. Multi Viscomindo**

Jl. Deplu Raya No. 7, Bintaro, Pesanggrahan – Jakarta 12330

Tel: +62 21 7376530 – Fax: +62 21 7363488

Email: sales@multiviscomindo.com